


Technical details broadloom

| | | | | | | |
|------------------------|-----------------------------|-------------------------|------------------------|-------------|---------------------|----------------------------------|
| Manufacturing type | Herstellungsart | Mode fabrication | Productie methode | | | tufted 1/10" |
| Construction | Struktur | Structure | Structuur | | | 2-ply saxony |
| Pile composition | Polmateriaal | Couche d'usure | Poolsamenstelling | | | 100% PA 6 - SDN - Econyl® |
| Secondary backing | Rückenausrüstung | Dossier | Rug | | | action backing |
| Pile weight | Poleinsatzgewicht | Poids de velour | Poolgewicht | ISO 2424 | g/m ² | 1.600 (+/-) |
| Total weight | Gesamtgewicht | Poids total | Totaal gewicht | ISO 8543 | g/m ² | 2.400 (+/-) |
| Pile height | Polhöhe | Hauteur du velours | Poolhoogte | ISO 1766 | mm | 8,5 (+/-) |
| Total height | Gesamtdicke | Epaisseur totale | Totale dikte | ISO 1765 | mm | 10,0 (+/-) |
| Tuft density | Noppenzahl | Nombre de touffes | Aantal punten | ISO 1763 | /m ² | 220.000 (+/-) |
| Width | Breite | Largeur | Breedte | | cm | 400-500 (+/-) |
| Classification | Klassifikation | Classement | Gebruiksklasse | EN 1307 | | 33 heavy commercial |
| Comfort rating | Komfortklasse | Classement confort | Comfort klasse | EN 1307 | | LC 5 |
| Castor chair | Stuhrolleneignung | Chaise à roulettes | Rolstoelgeschikt | EN 985 | | A intensive |
| Stair suitability | Treppeneignung | Escaliers | Trappengeschikt | EN 1963 | | B occasional |
| Fire resistance | Brennverhalten | Comportement feu | Brandgedrag | EN 13501-1 | | CFI-S1 glued |
| Permanent antistatic | Permanent Antistatisch | Antistatique permanent | Permanent antistatisch | ISO 6356 | kV | ≤ 2,0 |
| Transversal resistance | Durchgangswiderstand | Résistance transversale | Doorgangsweerstand | ISO 10965 | Ω | ≤ 10⁹ |
| Thermal resistance | Wärmedurchlaßwiderstand | Résistance thermique | Warmteoorlaatweerstand | ISO 8302 | m ² /K/W | 0,114 TOG 1,14 |
| Sound absorption | Schallabsorptionsgrad | Absorption phonique | Geluidsabsorptie | ISO 354 | α _w | 0,25 |
| Impact sound reduction | Trittschallverbesserungsmaß | Isolation phonique | Geluidsisolatie | ISO 10140 | ΔL _w | 30 dB |
| | | | | | ISO 10140 | ΔL |
| Light Fastness | Lichtechtheit | Solidité à la lumière | Lichtechtheid | ISO 105 B02 | | 7-8 |
| Rubbing fastness | Reibechtheit | Solidité au frottement | Wrijftechtheid | ISO 105 X12 | | ≥ 5 |

Scan the QR code and discover the collection.



EN 1307
for use as floorcovering in buildings (EN 14041) according to the manufacturer's specification

EN 14041
DOP 00620A-001

moth proof

CE



ECONYL®
ENDLESS POSSIBILITIES



TWISE

