



Technical details carpet tiles							
Manufacturing type	Herstellungsart	Mode fabrication	Productie methode	<b>tufted 1/10"</b>			
Construction	Struktur	Structure	Structuur	<b>structured loop pile</b>			
Pile composition	Polmaterial	Couche d'usure	Poolsamenstelling	<b>100% PA 6</b>			
Dye method	Farbgestaltung	Coloration	Kleurverwerking	<b>solution dyed</b>			
Primary backing	Trägermaterial	Premier dossier	Tuftdoek	<b>polyester fleece</b>			
Secondary backing	Rückenausrüstung	Dossier	Rug	<b>GREENBASE modified bitumen</b>			
Pile weight	Poleinsatzgewicht	Poids de velour	Poolgewicht	ISO 2424	g/m <sup>2</sup>	<b>650</b>	(+/-)
Total weight	Gesamtgewicht	Poids total	Totaal gewicht	ISO 8543	g/m <sup>2</sup>	<b>4.300</b>	(+/-)
Pile height	Polhöhe	Hauteur du velours	Poolhoogte	ISO 1766	mm	<b>4,0</b>	(+/-)
Total height	Gesamtdicke	Epaisseur totale	Totale dikte	ISO 1765	mm	<b>7,0</b>	(+/-)
Tuft density	Noppenzahl	Nombre de touffes	Aantal punten	ISO 1763	/m <sup>2</sup>	<b>191.000</b>	(+/-)
Size	Abmessung	Dimension	Afmeting		cm	<b>50 x 50</b>	
Packing	Verpackung	Emballage	Verpakking			<b>20 per box</b>	<b>5 m<sup>2</sup></b>
Classification	Klassifikation	Classement	Gebruiksklasse	EN 1307		<b>33</b>	<b>heavy commercial</b>
Comfort rating	Komfortklasse	Classement confort	Comfort klasse	EN 1307		<b>LC 1</b>	
Castor chair	Stuhlrolleneignung	Chaise à roulettes	Rolstoelgeschikt	EN 985		<b>A</b>	<b>intensive</b>
Dimensional stability	Dimensionstabilität	Stabilité dimensionnelle	Dimensionele stabiliteit	EN 986		<b>≤ 0,2%</b>	
Fire resistance	Brennverhalten	Comportement feu	Brandgedrag	EN 13501-1		<b>Bfl-S1</b>	loose laid
Permanent antistatic	Permanent Antistatisch	Antistatique permanent	Permanent antistatisch	ISO 6356	kV	<b>≤ 2,0</b>	
Transversal resistance	Durchgangswiderstand	Résistance transversale	Doorgangsweerstand	ISO 10965	Ω	<b>≤ 10<sup>9</sup></b>	
Thermal resistance	Wärmedurchlaßwiderstand	Résistance thermique	Warmtedoorlaatweerstand	ISO 8302	m <sup>2</sup> /K/W	<b>0,072</b>	
Sound absorption	Schallabsorptionsgrad	Absorption phonique	Geluidsabsorptie	ISO 354	α <sub>w</sub>	<b>0,15</b>	
Impact sound reduction	Trittschallverbesserungsmaß	Isolation phonique	Geluidsisolatie	ISO 10140	ΔL <sub>w</sub>	<b>26 dB</b>	
						ISO 10140	ΔL
Light fastness	Lichtechtheit	Solidité à la lumière	Lichtechtheid	ISO 105 B02		<b>8</b>	
Rubbing fastness	Reibechtheit	Solidité au frottement	Wrijfchtheid	ISO 105 X12		<b>4-5</b>	wet/dry
Water fastness	Wasserechtheit	Solidité à l'eau	Waterechtheid	ISO 105 E01		<b>5</b>	colour/staining
Pattern repeat	Musterwiederholung	Répétition du motif	Patroonherhaling		W x H	<b>206 x 172</b>	

Scan the QR code and go to the productpage on the website.



EN 1307  
for use as floorcovering  
in buildings (EN 14041)  
according to the  
manufacturer's specification

CE  
22  
EN 14041  
DOP 000572T-003

